# Product datasheet Characteristics

## EVH2S3P04K

EVlink Wallbox - 3.7 kW - socket-outlet T2 with shutter - charging station





IVICIII		
Range	EVlink	,
Product name	EVlink Wallbox	
Product or component type	Charging station	
Device short name	EVH2	
Poles description	1P + N	
Mounting mode	Wall-mounted	
Offer type	Standard	
Nominal output power	3.7 kW 16 A	
Socket number	1	
Output type	Socket-outlet T2 with shutter	-
Access control system	Key	-

### Complementary

[Us] rated supply voltage	220240 V AC 50/60 Hz	÷
Earthing system	TT TN	20.00 10.0
Number of inputs	1	
Input type	Contact for power limitation Contact for delayed charging	
Control type	white button, function: stop/restart     green button, function: cable unlocking	ve per pue
Local signalling	1 multi-colour LED, function: status indication	
Height	480 mm	
Width	331.5 mm	
Depth	170 mm	
Product weight	5.6 kg	
Colour	Grey RAL 7016 White RAL 9003	ii T
Standards	IEC 62196-2	

	IEC 62196-1 IEC 61851-22 IEC 61851-1	
Product certifications	CE	
	СВ	

### Environment

IP degree of protection	IP54 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Ambient air temperature for operation	-3050 °C
Ambient air temperature for storage	-4080 °C
Relative humidity	595 %

### Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1514 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Available	