



Main

| | |
|---------------------------|---|
| Range | EVlink |
| Product name | EVlink parking |
| Product or component type | Charging station |
| Device short name | EVW2 |
| Poles description | 1P + N for control circuit 1P + N for power circuit |
| Mounting mode | Wall-mounted |
| Offer type | Standard |
| Rated supply voltage | 230 V AC 50/60 Hz power circuit 220...240 V AC 50/60 Hz control circuit |
| Earthing system | TN IT TT |
| Socket-outlet number | 2 |
| Socket-outlet type | Right: T2 with shutter / silver plated contacts Left: T2 with shutter / silver plated contacts |
| Maximum supply current | 32 A for T2 with shutter |
| Max power | 7 kW for T2 with shutter |
| Access control system | Badge RFID conforming to ISO/IEC 14443 Badge RFID conforming to ISO/IEC 15693 |

Complementary

| | |
|-----------------------------|--|
| Control type | 2 red push-button, function: stop 2 green illuminated push-button, function: start/unlock flap |
| Local signalling | On charge: 2 LED (green) (flashing) on side Available: 2 LED (green) on front Reserved: 2 LED (orange) on front Not operational: 2 LED (red) on front |
| Communication port protocol | OCPP 1.6 |
| Configuration /Architecture | Clustured architecture Standalone |

| | |
|---------------------------|--|
| Operation and maintenance | Diagnosis capabilities Circuit breaker status Postponed charge Charge detail records User privilege configuration Load management |
| Web server | Embedded |
| Ethernet service | Configuration via web server |
| Standards | IEC 61851-22 IEC 61851-1 |
| Product certifications | ZE Ready EV Ready CB CE |
| Height | 620 mm |
| Width | 413 mm |
| Depth | 256 mm |
| Net weight | 33 kg |
| Colour | Front: white (RAL 9003) Side: grey (RAL 7016) |

Environment

| | |
|---------------------------------------|---|
| IP degree of protection | IP54 off load conforming to IEC 61851-1 IP54 on load conforming to IEC 61851-1 |
| IK degree of protection | IK10 charging station conforming to IEC 61851-22 IK10 socket-outlet conforming to IEC 61851-22 |
| Ambient air temperature for operation | -30...50 °C conforming to IEC 61851-22 |
| Ambient air temperature for storage | -40...80 °C |
| Operating altitude | 0...2000 m conforming to IEC 61851-22 |
| Relative humidity | 0...95 % |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Not applicable, out of EU RoHS legal scope EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | Download RoHS China Declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |